

## Stainless steel rope, Ø 16 mm, m/l



### Use:

- Used by the sea or outdoors with specific customary requirements.

### Technical properties

- Metallic central core - Right hand lay.
- Available option: sleeved thimble loop.
- Stainless steel single eye hook recommended.

### Technical characteristics of Stainless steel rope, Ø 16 mm, m/l

References	CB16INOX
Mini. breaking load kg	
Theoretical weight kg/m	
Pulling working load kg	
Lifting working load wire rope kg	
Construction	
Wire rope Ø mm	16

## Technical characteristics of the other models of the range

References	CB2_5INOX	CB3INOX	CB4INOX	CB5INOX	CB6INOX
Mini. breaking load kg	340	460	830	1300	1880
Theoretical weight kg/m	0,024	0,034	0,061	0,095	0,138
Pulling working load kg	113	153	277	433	627
Lifting working load wire rope kg	68	92	166	260	376
Construction	7 x 19	7 x 19	7 x 19	7 x 19	7 x 19
Wire rope Ø mm	2,5	3	4	5	6

References	CB7INOX	CB8INOX	CB9INOX	CB10INOX	CB12INOX
Mini. breaking load kg	2560	3330	4220	5210	7500
Theoretical weight kg/m	0,187	0,243	0,308	0,381	0,548
Pulling working load kg	853	1110	1407	1737	2500
Lifting working load wire rope kg	512	666	844	1042	1500
Construction	7 x 19	7 x 19	7 x 19	7 x 19	7 x 19
Wire rope Ø mm	7	8	9	10	11,5

References	CB14INOX	CB16INOX	CB18INOX	
Mini. breaking load kg	10200		18414	On request
Theoretical weight kg/m	0,746		1,230	On request
Pulling working load kg	3400		6138	On request
Lifting working load wire rope kg	2040		3683	On request
Construction	7 x 19		7 x 19	On request
Wire rope Ø mm	14	16	18	>18



**HUCHEZ**  
 4, rue Michel HAMMID  
 60420 FERRIERES – France  
 ☎ +33 (0) 3 44 51 11 33  
 🌐 [www.huchez.com](http://www.huchez.com)  
 ✉ [contact@huchez.fr](mailto:contact@huchez.fr)



SERVICE CLIENTS  
 ATENCIO AL CLIENTE  
 KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!  
 To know more, please contact us!  
 Para más información, póngase en contacto con nosotros!  
 Für weitere Informationen können Sie sich gerne an uns wenden!