

NEW IN 2020



RANGE OF VEHICLE WINCHES BY RUNVA

ELECTRIC AND HYDRAULIC WINCHES

CONTACT :

Sales team

☎ : +33 (0)344 511 133 - ✉ : contact@huchez.fr



 **HUCHEZ**

huchez.com





FOR ATV/UTV (QUADS AND OTHER LEISURE VEHICLES...)



12V ELECTRIC WINCHES EP3500 AND EP4500

Capacity: from 1588 to 2041 kg – Speed: up to 1.4 m/min

Supplied with wire rope or textile rope and hook



FOR OFFROAD VEHICLES (4X4...)



12/24V ELECTRIC WINCHES EB9500 AND EB12500

Capacity: from 4309 to 5670 kg – Speed: up to 2.8 m/min

Supplied with wire rope or textile rope and hook



**FOR TRUCKS, TOW TRUCKS, CAR CARRIER
TRAILERS, EMERGENCY VEHICLES...**



12/24V ELECTRIC WINCHES EN17500 AND EB20000

Capacity: from 7938 to 9072 kg – Speed: up to 1.3m/min

Supplied with wire rope and hook



HYDRAULIC WINCHES HN15000Y1D

Capacity: 6804 kg – Speed: up to 6 m/min

Wire rope and hook in option

TECHNICAL CHARACTERISTICS

FOR ATV/UTV (QUADS...)

References	EP3500U12V	EP4500U12V
Rated line pull 1st layer kg	1588	2041
Amps on 1st layer (without load/at nominal load)	20/200	28/220
Motor kW	2.4	2.5
Speed on 1st layer (without load/at nominal load) m/min	3.2/1.4	3.9/1.4
Rope Ø (wire/textile) supplied with the winch mm	5.4/5	6/6
Length of rope (wire/textile) supplied m	12.8/15	14.5/15
Weight kg	10	15.5

FOR OFFROAD VEHICLES (4X4...)

References	EB9500U12V	EB9500U24V	EB12500U12V	EB12500U24V
Rated line pull 1st layer kg	4309	4309	5670	5670
Amps on 1st layer (without load/at nominal load)	75/380	65/270	75/490	60/200
Motor kW	4.6	6.5	5.9	4.8
Speed on 1st layer (without load/at nominal load) m/min	9.8/2	10.5/2.8	10/1.6	10/1.6
Rope Ø (wire/textile) supplied with the winch mm	9.2/9	9.2/9	10.2/-	10.2/-
Length of rope (wire/textile) supplied m	26/25	26/25	25,5/-	25,5/-
Weight kg	37.5	37.5	42.9	42.9

FOR TRUCKS, TOW TRUCKS, CAR CARRIER TRAILERS ...

References	EN17500U12V	EN17500U24V	EB20000U12V	EB20000U24V
Rated line pull 1st layer kg	7938	7938	9072	9072
Amps on 1st layer (without load/at nominal load)	100/450	40/250	60/430	35/253
Motor kW	5.4	6.0	5.5	6.1
Speed on 1st layer (without load/at nominal load) m/min	6/0.9	4.4/1.2	8/1.2	8.4/1.3
Wire rope Ø supplied with the winch mm	12	12	12	12
Length of wire rope supplied m	26.5	26.5	26.5	26.5
Weight kg	67	67	70	70

Reference	HN15000IY1D
Rated line pull 1st layer kg	6804
Reducer	Planetary gears
Maxi. oil pressure bars	13 Mpa
Maxi. oil flow l/min	60
Brake	Hydraulic
Speed on 1st layer without load m/min	6
Wire rope Ø mm (in option)	12
Length of wire rope m	26.5
Weight kg	60

CONTACT :

Sales team

☎ : +33 (0) 344 511 133 - ✉ : contact@hucnez.fr